



FORCE 165 230V ACX PLASTIC CARRY CASE



Overview

FORCE 165 230V ACX PLASTIC CARRY CASE

cod. 815857

MMA inverter, electrode welding machine in direct current (DC).

Usable electrodes: rutile, basic, stainless steel, cast iron, etc.

Features:

- Reduced weight and dimensions
- High welding current stability in spite of mains voltage fluctuations
- Arc force, hot start and anti-stick devices
- Thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator ($\pm 15\%$) protections.

Complete with MMA welding accessories and plastic carry case.



MMA DC



CE MARKING



TÜV CERTIFICATION



1 PH 230V



EAC CERTIFICATION

Technical data



CODE 815857



MAX ABSORBED CURRENT 31 A



PROTECTION DEGREE IP21



SINGLE PHASE MAINS VOLTAGE 230 V



MAX ABSORBED POWER 4,1 kW



DIMENSIONS 38 - 42 - 17 cm



MAINS FREQUENCY 50 / 60 Hz



MOTORGENERATOR MINIMUM POWER 6 kW



WEIGHT 5,5 kg



CURRENT RANGE 10 - 150 A



MAINS FUSE 16 A



EAN CODE 800489778955 2



FORCE 165 230V ACX PLASTIC CARRY CASE

	%USE (20°C USE) 60% % - 150A		EFFICIENCY 82 %		PIECES/PALLET 36 pz/pallet
	MAX CURRENT 140 A - 7%		POWER FACTOR (cosphi) 0,6		PIECES/PALLET - B 30 pz/pallet - B
	MAX NO LOAD VOLTAGE 72 V		D. USABLE ELECTRODES IN DC 1,6 - 4 mm		

(*)%USE:DATUM CREATED BY TELWIN,

Included Accessories

	CABLE 16 MMQ 1,8 M - DINSE 25 - 124508		MASK - 712250
	PLASTIC CARRY CASE - 322800		FILTER 51X108 - 712257
	TOLEDO 250 WORK CLAMP 250A - 712030		DALLAS 300 ELECTRODE HOLDER 300A - 712260
	SLAG REMOVER - 712139		