



TECHNOLOGY 238 XT CE/MPGE 230V ACX+CASE



Overview

TECHNOLOGY 238 XT CE/MPGE 230V ACX+CASE

cod. 816252

MMA and TIG inverter, electrode welding machine in direct current (DC) with scratch striking.

Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron, cellulosic, etc.

Recommended for motorgenerators, this model grants high performance despite power supply instability, thanks to the MPGE multiprotections: control device of the wave form, filter against input peaks, stabilization of oscillations. Robust and impact resistant.

Features:

- compact and light
- 50 Ø dinse
- high welding current stability in spite of mains voltage fluctuations
- regulation of arc force and hot start according to the type of electrode in use
- anti-stick device
- thermostatic, overvoltage, undervoltage, overcurrent protections.

Complete with MMA welding accessories and aluminium carry case.



MMA TIG DC SCRATCH



CE MARKING



EAC CERTIFICATION



1 PH 230V

Technical data

CODE 816252	MAX ABSORBED CURRENT 39 A	POWER FACTOR (cosphi) 0,7
SINGLE PHASE MAINS VOLTAGE 230 V	ABSORBED CURRENT AT 60% - MAX 20 A	D. USABLE ELECTRODES IN DC 1,6 - 4 mm
MAINS FREQUENCY 50 / 60 Hz	MAX ABSORBED POWER 6,3 kW	PROTECTION DEGREE IP23



TECHNOLOGY 238 XT CE/MPGE 230V ACX+CASE

	CURRENT RANGE 5 - 200 A		ABSORBED POWER AT 60% 3 kW		DIMENSIONS 37,5 - 50 - 22 cm
	MAX CURRENT 200 A - 35 %		MOTORGGENERATOR MINIMUM POWER 10 kW		WEIGHT 10,55 kg
	CURRENT AT 60% 140 A		EFFICIENCY 87 %		EAN CODE 800489716580 6
	MAX NO LOAD VOLTAGE 80 V				

Included Accessories



null - 712231



null - 712260