

DATA SHEET

RTF-X TIG 19pol 5 m

090-008855-00005



- Foot-operated remote control with pre-fitted connection cable
- Infinitely adjustable welding current (0% to 100%) depending on the main current preselected at the welding machine.
- Operating point setting directly at the site of welding
- **Stainless steel clip (picture 2)**
- Easily adjust the position of the remote control with your foot
- One-sided opening allows easy yet secure positioning of the foot on the tread surface
- Tool-free assembly on both sides of the remote control
- **Tread surface (picture 3)**
- The large tread surface ensures safe and comfortable operation (L= 312 mm W1=117 mm W2=142 mm)
- The slip-proof coating prevents slipping, even with wet or dirty soles
- A raised edge at the heel prevents accidental slipping from the tread surface and can also be used to pull the remote control back
- Suitable for any shoe size
- **Rubber feet (picture 4)**
- Secure positioning on any surface
- Prevent accidental movement of the remote control
- Can be quickly replaced when worn down with no need to open the casing
- **The high-quality connection cable is fed into the remote control through a robust anti-kink device. This ensures protection from damage, even under tough conditions (picture 5)**
- **Large, sturdy hook for transport on EWM machines and Trolley transport systems or standard transport carts (picture 6)**

Cable length	5 m
Connection	19-pole
Dimensions (L x B x H)	377 mm x 154 mm x 228 mm
Weight	2.9 kg
Test mark	CE EAC UK CA