

# DATA SHEET

## Phoenix XQ 400 puls CW HP


090-005648-00017



- MIG/MAG inverter welding machine, pulse, with integrated wire feeder
- Perfect MIG/MAG weld seams even with long welding leads
- Synergic control with one-knob operation

**all in**

**No need to purchase additional characteristics – all characteristics for this machine type are included in the scope of delivery ex works**

- With innovative EWM Synergic characteristics rootArc<sup>®</sup> XQ/rootArc<sup>®</sup> puls XQ, forceArc<sup>®</sup> XQ/forceArc<sup>®</sup> puls XQ, pulse/superPuls and Positionweld for aluminium
- To find out more about our high-tech MIG/MAG arcs, please click on XQ-Process 
- Synergic characteristics for MIG/MAG standard or pulsed welding for steel/CrNi/aluminium
- Synergic characteristics for flux-cored wires
- Non Synergic operation for manual setting of welding parameters
- Also suitable for MMA welding, TIG welding and gouging
- Individually configurable programs for JOBs (welding tasks)
- Powerful, high-precision EWM eFeed 4-roll wire feeder to reliably feed all solid and flux cored wires
- Adjustable start and end-crater functions
- Infinitely adjustable arc dynamics (choke effect)

### • Your benefits

- flexFit casing system: Many accessory parts and options can be fixed to the welding machine using conventional slot nuts
- LED information bar: Indicates the current operating status
- Energy-saving thanks to high efficiency and standby function
- Best suited for use with long hose packages
- Connection capability for remote control and function torch
- Easy, tool-free change of welding polarity
- Insulated wire space
- IP23 spray water protected
- Optional network connectivity with the ewm Xnet software via an integrated or external gateway
- PC interface for PC300 XQ software
- The high 1500 W cooling capacity, high-performance centrifugal pump and 8-litre coolant tank make for excellent torch cooling, resulting in cost savings on consumables
- Free WPQR package for certification up to and including EXC2 in accordance with EN 1090 and for welding of unalloyed steels up to and including S355

# DATA SHEET

## Phoenix XQ 400 puls CW HP

Version	Phoenix XQ 400 puls C W HP R1 5m 19P
Setting range for welding current	5 A - 400 A
Duty cycle 40 °C	400 A / 60 % 350 A / 80 % 320 A / 100 %
Open circuit voltage	82 V
Mains voltage (ex works)	3 x 380 V - 400 V
Mains voltage (possible)	3 x 440 V - 460 V
Mains voltage (possible)	3 x 480 V - 500 V
Mains tolerances (ex works)	-25 % up to +20 %
Mains frequency	50 Hz / 60 Hz
Recommended generator power	23.2 kVA
Efficiency	90 %
Power consumption Pi	32 W
Wire feed speed	0.5 m/min - 25 m/min 19.685 ipm - 984.253 ipm
Factory-installed roll equipment	1,0-1,2 mm UNI / Steel
Spool diameter	D200/D300
Torch connection	Euro torch connector
Cooling capacity at 1 l/min.	1500 W
Pump pressure	3.5 bar
Tank capacity	8 l
Protection classification	IP23
Test mark	CE UK EAC S
EMC class	A
Dimensions (L x B x H)	1150 mm x 678 mm x 972 mm 45.3 inch x 26.7 inch x 38.3 inch
Weight	128 kg / 282.2 lbs
Standards	IEC 60974-1, -2, -5 and -10 CL.A

### Configurations

Item no.	Designation
090-005648-00000	Phoenix XQ 400 puls C. Multiprocess MIG/MAG pulse welding machine including all characteristics and welding processes,
092-003303-00000	OW F06W. Water cooling
092-003312-00000	OW AIF F06. 19-pole interface for automated welding
092-003314-00000	OW NDGC F.06 C. No gas control
092-003316-00000	OW F06R1. Wheel kit with single cylinder mount
092-003349-00000	OW MCord 6 mm <sup>2</sup> 5m. Mains connection lead, 5 m
092-003522-00000	OW HP-XQ. HP-XQ control
092-003749-00000	OW NVRD F06 C. No open circuit voltage reduction
092-003843-00000	OW NWHS F06 C. No wire spool heating
092-003844-00000	OW N2 DV XQ C. Without connection capability for an external wire feeder to XQ compact welding machines
092-008215-00000	OW CEE 32A. Mains plug, assembled