



SUPERIOR TIG 322 AC/DC-HF/LIFT 400V+ACC.



Overview

SUPERIOR TIG 322 AC/DC-HF/LIFT 400V+ACC.

cod. 816130

Microprocessor controlled, TIG (high frequency HF or LIFT striking), PULSE TIG and MMA inverter welding machine in direct and alternating current (AC/DC).

Use with a wide range of materials such as steel, stainless steel, aluminium, titanium, copper, nickel, magnesium and their alloys.

Features:

- pulse and EASY pulse operation
- 9 customized welding programmes
- TIG regulations: bi-level, start up/end current, spot welding time, pre/post gas, current up/down slope, balance DC/AC, square wave frequency
- MMA regulations: arc force and hot start according to the type of electrode in use
- anti-stick device
- remote control and G.R.A. water cooling connector
- storage on on-board E2PROM of the last 10 alarms
- thermostatic, overvoltage, undervoltage, inside dirtiness, overcurrent, phase failure, water cooling unit protections.

Complete with TIG welding accessories.



REMOTE CONTROLS



CE MARKING



EAC CERTIFICATION

Technical data

CODE	CODE 816130	V _{0 DC}	MAX NO LOAD VOLTAGE 64 V	η	EFFICIENCY 85 V
V _{3PH}	THREE PHASE MAINS VOLTAGE 400 V	A _{MAX}	MAX ABSORBED CURRENT 15 A	φ	POWER FACTOR (cosphi) 0,92
F	MAINS FREQUENCY 50 / 60 Hz	A _{60% MAX}	ABSORBED CURRENT AT 60% - MAX 11 A	Ø _{DC MIN/MAX}	D. USABLE ELECTRODES IN DC 1,6 - 5 mm
A _{MIN MAX DC}	CURRENT RANGE 5 - 270 A	P _{MAX}	MAX ABSORBED POWER 10 kW	IP	PROTECTION DEGREE IP23



SUPERIOR TIG 322 AC/DC-HF/LIFT 400V+ACC.



MAX CURRENT DC (EN 60974-1) 270 @ 40 % A



ABSORBED POWER AT 60% 7 kW



DIMENSIONS 53 x 24 x 45 cm



DC CURRENT 215 A



MAINS FUSE 16 A



WEIGHT 34 kg

Included Accessories



ARGON GAS BOTTLE IT ADAPTOR - 432036



GAS REGULATOR 2 MANOMETERS 12 L\min - 722119



TOLEDO 300 WORK CLAMP - 712231

ST26 TIG TORCH AX50 4M - 742614

CABLE 25 MMQ 3 M ATLAS 50MMQ - 713504