



SUPERIOR TIG 422 AC/DC-HF/LIFT 400V AQUA



Overview

SUPERIOR TIG 422 AC/DC-HF/LIFT 400V AQUA

cod. 816135

Microprocessor controlled, TIG (high frequency HF or LIFT striking), PULSE TIG and MMA inverter welding machine in direct and alternating current (AC/DC).

Use with a wide range of materials such as steel, stainless steel, aluminium, titanium, copper, nickel, magnesium and their alloys.

Features:

- pulse and EASY pulse operation,
- 9 customized welding programmes,
- TIG regulations: bi-level, start up/end current, spot welding time, pre/post gas, current up/down slope, balance DC/AC, square wave frequency,
- MMA regulations: arc force and hot start according to the type of electrode in use,
- anti-stick device,
- remote control and G.R.A. water cooling connector,
- storage on on-board E2PROM of the last 10 alarms,
- thermostatic, overvoltage, undervoltage, inside dirtiness, overcurrent, phase failure, water cooling unit protections.

Complete with TIG welding accessories, trolley and G.R.A. Water cooling unit.



REMOTE CONTROLS



CE MARKING



EAC CERTIFICATION

Technical data

CODE	CODE 816135	V_{0 DC}	MAX NO LOAD VOLTAGE 64 V	η	EFFICIENCY 85 V
V_{3PH}	THREE PHASE MAINS VOLTAGE 400 V	A_{MAX}	MAX ABSORBED CURRENT 21 A	φ	POWER FACTOR (cosphi) 0,9
F	MAINS FREQUENCY 50 / 60 Hz	A_{MAX}^{60%}	ABSORBED CURRENT AT 60% - MAX 13 A	∅_{DC} MIN/MAX	D. USABLE ELECTRODES IN DC 1,6 - 6 mm
A_{MIN} / A_{MAX} DC	CURRENT RANGE 5 - 350 A	P_{MAX}	MAX ABSORBED POWER 14 kW	IP	PROTECTION DEGREE IP23



SUPERIOR TIG 422 AC/DC-HF/LIFT 400V AQUA



MAX CURRENT DC (EN 60974-1) 350 @ 35 % A



ABSORBED POWER AT 60% 8 kW



DIMENSIONS 93,5 x 50 x 119,5 cm



DC CURRENT 250 A



MAINS FUSE 16 A



WEIGHT 71 kg

Included Accessories



ARGON GAS BOTTLE IT ADAPTOR - 432036

ST18A TIG TORCH AX50 4M AQUA - 742615



TOLEDO 300 WORK CLAMP - 712231



G.R.A. 4000 WATER COOLING UNIT 230V - 802640

CABLE 25 MMQ 3 M ATLAS 50MMQ - 713504



TROLLEY - MONDIAL - 803072



GAS REGULATOR 2 MANOMETERS 12 L\min - 722119